

Lembar data produk

Spesifikasi



APC Back-UPS Pro, 1500VA/
865W, Tower, 230V, 10x IEC C13
outlets, AVR, LCD, User
Replaceable Battery

BR1500GI

Main

Main input voltage	230 V AC 1 phase
Input connection	IEC 60320 C13
Switching current capacity	10 A
Efficiency at full load	156...300 V adjustable 176...294 V
Input frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	865 W
Rated power in VA	1500 VA
Output connection	5 IEC 60320 C13 5 IEC 60320 C13 surge 2 IEC Jumpers
USB charging port	None
Crest factor	3 : 1
Maximum configurable power in VA	1500 VA
Maximum configurable power in W	865 W
Transfer time	10 ms typical : 12 ms maximum
UPS topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBC124

Grafik

Run-time	View Runtime Graph
Efisiensi	View Efficiency Graph

Complementary

Battery capacity	9.0 Ah
Battery type	Lead-acid internal included
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	USB port

Surge energy rating	441 J
Noise filtering	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
Number of cables	1
Color	Black
Height	301 mm
Width	112 mm
Depth	380 mm
Product weight	12.7 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Back-UPS Pro
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	A-Tick C-Tick CE GOST Telepermit TÜV
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP
Marking	GS Mark
Standard	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage relative humidity	0...95 %
Acoustic level	45 dBA
Operating altitude	0...30000 ft

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	24 V

Battery graph comment	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extendable runtime	0
Included battery module	0
Empty battery slot	0
Typical recharge time	8 h
RBC quantity	1
Battery life	3...5 year(s)
Battery charging power	23 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.000 cm
Package 1 Width	25.000 cm
Package 1 Length	49.000 cm
Package 1 Weight	14.000 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	24
Package 2 Height	132.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	351.000 kg
SCC14	10731304268748

Image of product / Alternate images

Alternative

