

Product datasheet

Specifications



APC Easy UPS 2200VA, Tower, 230V, 4 UNIVERSAL Outlets, AVR

BVG2200I-MSX

Main

Main input voltage	220...240 V AC 1 phase
Input connection	British 10.7 A
Input protection	Circuit breaker
Input frequency	50/60 Hz +/- 5 Hz indoor use only
Output voltage	230 V AC 1 phase
Rated power in W	1200 W
Rated power in VA	2200 VA
Output connection	4
Output connection	Universal
USB charging port	None
Maximum configurable power in W	1100 W
Output voltage tolerance	+/- 10 %
Transfer time	6 ms typical : 10 ms maximum
UPS topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Full load runtime	00:00:30 1200 W
Half load runtime	00:04:00 600 W

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery type	Lead-acid internal included
Control panel	LED Status display with on line : on battery
Emergency power off	No
Alarm	Alarm when on battery : distinctive low battery alarm : high temperature : overload continuous tone alarm
Surge energy rating	156 J
Color	Black
Height	182 mm
Width	130 mm

Depth	320 mm
Product weight	10.6 kg
USB compatible	No
Mounting mode	Desktop installation compact
Max runtime	0.6 min
Range of product	Easy UPS
Product or component type	Uninterruptible power supply (UPS)

Environment

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...3000 m
IP protection	IP20 indoor use only
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Acoustic level	< 45 dBA
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	VRLA
Extendable runtime	0
RBC quantity	0
Battery design life	3...5 year(s)
Battery life	3...5 year(s)
Battery charging power	28 W indoor use only

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.2 cm
Package 1 Width	13 cm
Package 1 Length	32 cm
Package 1 Weight	10.6 kg
SCC14	10731304769672

Technical Illustration

Dimensions





