



DETAILS:

Electromagnetic locks 600 series are known with its heavy duty together with its excellent holding force and remarkable standard feature.

The series are compliance to **CE Underwriters' Laboratories (UL)**. Products are manufactured under the highest quality control to achieve the commitment to customer who always satisfied with its durability, quality and reliability.

FEATURES:

- ✔ Dual voltage selectable
- ✔ Low current consumption
- ✔ Reliable holding force
- ✔ Hall effect sensor monitoring output
- ✔ Green/Red LED indication for EM Lock status
- ✔ Durable & silent operation
- ✔ Cosmeticize anodized aluminium casing
- ✔ Surge & spike protection PCB
- ✔ Anti-temper jam nuts
- ✔ Full range of optional brackets
- ✔ Anti residual magnetism kick off button

SPECIFICATION:

Voltage Input	12 VDC / 24 VDC
Current Draw	12V / 510mA; 24V / 285mA (±5%)
Holding Force	Up to 600 lbs (272 kg)
Hall Effect Contact	SPDT rated 1A at 24 VDC
Anti Rust Surface Treatment	Blue zinc plating
Operating Temperature	0~55°C (32~131°F)
Operating Humidity	0~95% (non condensing)
Weight	1.90 kg (±1%)
Dimension	Magnet: (L)250 x (W)42 x (T)25 mm Armature: (L)180 x (W)38 x (T)11 mm

