



## DETAILS:

Electromagnetic locks 600 Series are known with its heavy duty together with its excellent holding force and remarkable standard feature.


The series are compliance to CE and Underwriter's Laboratories (UL). Products are manufactured under the highest quality control to achieve the commitment to customer who always satisfied with its durability, quality and reliability.

## FEATURES:


- ✔ Dual voltage selectable (12VDC / 24VDC)
- ✔ Low current consumption
- ✔ Reliable holding force
- ✔ Durable & silence operation
- ✔ Cosmeticize anodized aluminum casing
- ✔ Surge & spike protection PCB
- ✔ Anti-temper jam nuts
- ✔ Full range of optional brackets
- ✔ Anti residual magnetism kick off button

## SPECIFICATION:

Voltage Input	12 VDC / 24 VDC
Current Draw	12V / 480mA; 24V / 240mA (±5%)
Holding Force	Up to 600 lbs (272 kg)
Anti Rust Surface Treatment	Blue zinc plating
Operating Temperature	0~55°C (32~131°F)
Operating Humidity	0~95% (non condensing)
Weight	1.90 kg (±1%)
Dimension	Magnet: (L)250 x (W)42 x (T)25 mm Armature: (L)180 x (W)38 x (T)11 mm



EM Lock Energized



EM Lock De-energized

