



MIFARE DESFIRE EV1

PC.DesfireEv1.2k / 4k / 8k



MIFARE DESFire EV1, a Common Criteria (EAL4+) certified product, is ideal for service providers wanting to use secure multi-application smart cards in public transport schemes, access management or closed-loop e-payment applications. It fully complies with the requirements for fast and highly secure data transmission, flexible memory organization and interoperability with existing infrastructure.

MIFARE DESFire EV1 is based on open global standards for both air interface and cryptographic methods. It is compliant to all 4 levels of ISO/IEC 14443A and uses optional ISO/IEC 7816-4 commands.

Featuring an on-chip backup management system and the mutual three-pass authentication, a MIFARE DESFire EV1 card can hold up to 28 different applications and 32 files per application. The size of each file is defined at the moment of its creation, making MIFARE DESFire EV1 a truly flexible and convenient product.

Additionally, an automatic anti-tear mechanism is available for all file types, which guarantees transaction-oriented data integrity. With MIFARE DESFire EV1, data transfer rates up to 848 kbit/s can be achieved, allowing fast data transmission.



MIFARE DESFIRE EV1

PC.DesfireEv1.2k / 4k / 8k

Key Feature

- Contactless transmission of data and powered by the RF-field (no battery needed)
- Operating distance: up to 100 mm (depending on power provided by the PCD and antenna geometry)
- Operating frequency: 13.56 MHz
- Fast data transfer: 106 kbit/s, 212 kbit/s, 424 kbit/s, 848 kbit/s
- High data integrity: 16/32 bit CRC, parity, bit coding, bit counting
- True deterministic anticollision
- 7 bytes unique identifier (cascade level 2 according to ISO/IEC 14443-3 and option for random ID)
- Uses ISO/IEC 14443-4 protocol



Ordering Information

PC.DesfireEv1.2k	EntryPass Mifare Desfire EV1 (2k Bytes)
PC.DesfireEv1.4k	EntryPass Mifare Desfire EV1 (4k Bytes)
PC.DesfireEv1.8k	EntryPass Mifare Desfire EV1 (8k Bytes)

MIFARE DESFIRE EV1

PC.DesfireEv1.2k / 4k / 8k

Technical Specification

Base Part Number	PC.DesfireEv1.2k	PC.DesfireEv1.4k	PC.DesfireEv1.8k
Operating Frequency	13.56 MHz		
RF Interface	ISO 14443 A, Parts 1-4 (DESFire EV1)		
Typical Maximum Read Range	DESFire: Up to 4" (10 cm)		
Transaction Time	< 100 ms		
Baud Rate	Activation at 106 kbps; Data transfer up to 848 kbps		
Memory Type	EEPROM 2 Kbytes	EEPROM 4 Kbytes	EEPROM 8 Kbytes
Memory Structure	Up to 28 applications, with up to 32 files per application		
Operating Temperature	-40 to 122°F (-40 to 50°C)		
Operating Humidity	5% - 95% Non-Condensing		
Write Endurance	100,000 cycles min		
Data Retention	10 years min		
Materials and Finish	Gloss white/white PVC or PVC/Polyester Composite		
Weight	0.20 oz (6.0 g)		
Programming	Factory or Field		
Card Marking	Inkjet standard, Laser Engraving optional		
Custom Graphics	Optional		
Magnetic Stripe	Optional		
Printable	Yes (white/white card)		



www.entrypass.net

Malaysia

No. 40, Jalan TPP 1/10, Taman Industri Puchong, Batu 12 Jalan Puchong, 47160 Puchong Selangor Darul Ehsan, Malaysia.
Tel : +603 8068 1929
Fax : +603 8062 6937
Email : info@entrypass.net

Singapore

No. 1, UBI View, #03-03, Focus ONE Building, Singapore 408555.
Tel : +65- 6841 7242
Fax : +65- 6841 3937
Email : info@entrypass.net

Indonesia

Rukan Puri Mutiara, Block BF No.17, Jln Griya Utama, Sunter Agung, Jakarta Utara, 14350, Indonesia.
Tel : +62 21 2937 6098
Email : indonesia@entrypass.net