

Model	ES105D	ES108D	ES105GD	ES108GD
Hardware specifications				
Ports	5*10/100Mbps RJ45 ports	8*10/100Mbps RJ45 ports	5*10/100/1000Mbps RJ45 ports	8*10/100/1000Mbps RJ45 ports
Operating mode	Half-duplex, full-duplex, auto-negotiation mode			
	Support auto MDI/MDIX			
Switching capacity	1Gbps	1.6Gbps	10Gbps	16Gbps
Package forwarding rate	744Kpps	1.19Mpps	7.44Mpps	11.9Mpps
MAC address	1K	2K	2K	8K
Power supply	External 5VDC 1.0A	External 5VDC 1.0A	External 5VDC 1.0A	External 5VDC 1.0A
Port Mode	N/A			
Power consumption	≤5W			
PoE	Not support			
Fan	N/A	N/A	N/A	N/A
Dimensions (W x D x H)	119 x 62 x 24mm	160 x 75 x 24mm	119 x 62 x 24mm	160 x 75 x 24mm
Operating temperature	0°C to 40°C			
Storage temperature	-40°C to 70°C			
Operating humidity	10% to 90% RH			
Storage humidity	5% to 90% RH			



4 Ordering Information

Model	Description
RG-ES106D-P	4 x 100M copper ports and 2 x 100M uplink copper ports: 4 ports for PoE/PoE+, with the maximum PoE power up to 58 W; unmanaged switch; desktop type.
RG-ES110D-P	8 x 100M copper ports and 2 x 1000M uplink copper ports: 8 ports for PoE/PoE+, with the maximum PoE power up to 110 W; unmanaged switch; desktop type.
RG-ES118S-LP	16 x 100M copper ports and 2 x 1000M uplink SFP combo ports: 16 ports for PoE/PoE+, with the maximum PoE power up to 120 W; unmanaged switch; rack-mount supported.
RG-ES126S-LP	24 x 100M copper ports, 1 x 1000M uplink copper port, and 1 x 1000M uplink SFP combo port: 24 ports for PoE/PoE+, with the maximum PoE power up to 180 W; unmanaged switch; rack-mount supported.
RG-ES109G-LP-L	Unmanaged Switch, 9 10/100/1000BASE-T ports, external AC-DC power adaptor, support PoE/ PoE+, PoE power budget: 54W
RG-ES126G-LP-L	Unmanaged Switch, 24 10/100/1000BASE-T ports, 2 1000M SFP ports, AC power supply, support PoE/ PoE+, PoE power budget: 180W
RG-ES126G-P-L	Unmanaged Switch, 24 10/100/1000BASE-T ports, 2 1000M SFP ports, AC power supply, support PoE/ PoE+, PoE power budget: 180W
RG-ES105D	5 10/100M RJ45 ports, metal casing, external 5VDC 1.0A power adapter
RG-ES108D	8 10/100M RJ45 ports, metal casing, external 5VDC 1.0A power adapter
RG-ES105GD	5 10/100/1000M RJ45 ports, metal casing, external 5VDC 1.0A power adapter
RG-ES108GD	8 10/100/1000M RJ45 ports, metal casing, external 5VDC 1.0A power adapter
RG-ES116G	16 10/100/1000M copper ports; unmanaged switch; desktop type; rack-mount supported.
RG-ES124GD	24 10/100/1000M copper ports; unmanaged switch; desktop type; rack-mount supported.