

# Product datasheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1500RMI2UC

## Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead time** Usually in Stock

## Main

**Product or component type** Uninterruptible power supply (UPS)

## Complementary

**Communication port type** SmartConnect Ethernet port  
SmartSlot

**Software package** SmartConnect software for remote power monitoring feature availability varies by terms of use

## Batteries & Runtime

**Run Time** [View Runtime Graph](#)

**Efficiency** [View Efficiency Graph](#)

**Battery type** Lead-acid battery

**Additional information** Configurable for 220 : 230 or 240 nominal output voltage

**Extended runtime** 0

**Number of battery filled slots** 0

**Number of battery free slots** 0

**Battery recharge time** 3 h

**Number of battery replacement quantity** 1

**Battery life** 3...5 year(s)

**Replacement battery** [APCRBC159](#)

**Battery charger power** 144 W rated

## General

**Provided equipment** Installation guide  
Rack mounting support rails  
USB cable

**Number of power module** 0

**Number of power module filled slots** 0

Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

## Physical

Number of rack unit	2U
Colour	Black
Height	8.6 cm
Width	43.2 cm
Depth	47.7 cm
Product weight	26.1 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

## Input

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Input Connection Type	IEC 320 C14
Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	1000 W
Rated power in VA	1500 VA
output connection type	4 IEC 320 C13 2 IEC Jumpers C13
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	1500 VA
Maximum configurable power in W	1000 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

<b>Product certifications</b>	CE EAC RCM TÜV VDE UK PSTI
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

<b>Acoustic level</b>	46 dBA
<b>Heat dissipation</b>	90 Btu/h
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0.0000000000...15240.0000000000 m
<b>Relative humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Communications & Management

<b>control panel</b>	Multifunction LCD status and control console
<b>Emergency power off</b>	Optional
<b>Free slots</b>	1
<b>Communication port support</b>	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

<b>Surge energy rate</b>	459 J
<b>Noise suppression</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	25.095 cm
<b>Package 1 Width</b>	59.385 cm
<b>Package 1 Length</b>	60.325 cm
<b>Package 1 Weight</b>	38.240 kg

## Contractual warranty

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **1417**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **B2b22a56-41f2-497e-9ea6-cf093b3b8bd3**

REACH Regulation [REACH Declaration](#)

### Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery **User replaceable**

Take-back **Yes**

Image of product / Alternate images

Alternative

---



