

Product datasheet

Specifications



APC Easy UPS On-Line, 1000VA/900W, Rackmount 4U, 230V, 4x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime, W/ rail kit

SRV1KRILRK-E

Overview

Presentation High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

Lead time Usually in Stock

Main

Main Input Voltage 230 V

Product or component type Uninterruptible power supply (UPS)

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 900 W

Rated power in VA 1000 VA

Input Connection Type IEC 60320 C14

output connection type 4 IEC 60320 C13

Number of rack unit 4U

Number of cables 1

Provided equipment 1 IEC 60320 C13 to Schuko power cable
1 IEC 60320 C13 to C14 power cable
1 USB cable
1 RS-232 configuration cable
2 rack mounting brackets
2 rack mounting support rails
1 external battery pack
1 battery cable
user manual

Range of product Easy UPS On-Line

Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Battery type Lead-acid battery

Battery voltage 36 V

Extended runtime 1

Number of battery filled slots 0

Number of battery free slots	0
Battery recharge time	4.5 h
Battery life	3...5 year(s)
Battery charger power	262 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black (RAL 7010)
Height	17.2 cm
Width	43.8 cm
Depth	41.2 cm
Product weight	27.1 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	No
Mounting position	Horizontal

Input

Input voltage limits	105...300 V 40% load 180...285 V full load
Network frequency	40...70 Hz auto sensing

Output

Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

Conformance

Product certifications	CE UKCA TISI
------------------------	--------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	53 dBA
Heat dissipation	380 Btu/h
IP degree of protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
control panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge energy rate	600 J
--------------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	3
Package 1 Height	48 cm
Package 1 Width	50 cm
Package 1 Length	60 cm
Package 1 Weight	33.1 kg

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Take-back

No

WEEE


 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



