

## Key Features

- 2<sup>nd</sup> gen. LED Technology, Cinema SuperColor+ (125% Rec.709), Mercury free, Instant on/off
- Cinematic colors covering 125% Rec.709, high contrast ratio for sharp images
- Dual HDMI 2.0b : Supports 4K UHD, HDR, HLG content
- Easy Installation : 360° tilt angle projection, Portrait mode, H/V Keystone, 1.2x Zoom
- 6X Fast Input : Super Low input lag 8ms, perfect for gaming



## Product Description

The ViewSonic LS600HD is a 3,000 ANSI Lumens High Brightness Lamp Free 1080p Projector for home and business. Adopting the 2nd generation LED technology, it frees users from frequent lamp replacement and toxic mercury, offers amazing 30,000 hours long lifespan and cinematic colors covering 125% Rec.709, as well as the convenient instant power on/off ability. Dual HDMI 2.0b ports ensure movie lovers' access to 4K UHD/HDR/HLG high quality content. Gamers can revel in the speed and thrill realized by the 6X Fast Input, taking their gaming experience to the next level. Enjoy all the amazing experience this projector has to offer with hassle-free setup. The 360° tilt angle projection, portrait mode, 1.2x zoom lens, H/V Keystone as well as 4 Corner adjustment have you back-upped.

**Visit Us** ■ [www.viewsonic.com](http://www.viewsonic.com)

## SPECIFICATION

Native Resolution:	1920x1080
DMD Type:	DC3
Brightness:	3000 (ANSI Lumens)
Contrast Ratio:	3000000:1
Display Color:	1.07 Billion Colors
Light Source Type:	LED
Light Source Life (hours) with Normal Mode:	up to 30000
Lamp Watt:	RGBB LED
Lens:	F=1.6-1.75, f=19.16-23.02mm
Projection Offset:	83%+/-9%
Throw Ratio:	1.3-1.56
Optical Zoom:	1.2X
Digital Zoom:	0.8-2.0x
Keystone:	H:+/-40° , V:+/-40°
Audible Noise (Normal):	31dB
Audible Noise (Eco):	25dB
Input Lag:	8ms
Resolution Support:	VGA(640 x 480) to 4K UHD (340 x 2160)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~135KHz
Vertical Scan Rate:	23~120Hz

## INPUT

Computer in (share with component):	1
Composite:	1
HDMI:	2 , (HDMI 2.0b, HDCP 2.2)
Audio-in (3.5mm):	1

## OUTPUT

Audio out (3.5mm):	1
Speaker:	10W
USB Type A (Power):	1 (5V/ 1.5A)

## CONTROL

RS232 (DB 9-pin male):	1
------------------------	---

## OTHERS

Operating Temperature:	0~40°C
------------------------	--------

OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, total 23 languages
---------------	---

## STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1