

ViewSonic® LCD DISPLAY VA2223-H

Key Features

- HDMI and VGA input
- Flicker-Free and Blue Light Filter
- VESA mountable
- ViewMode technology
- Eco-mode



Product Description

The ViewSonic VA2223-H is a cost-effective 22" Full HD monitor with HDMI and VGA input that is ideal for business or home usage. It features 1080p resolution which delivers stunning image quality and more detailed content. ViewSonic's exclusive ViewMode feature provides intuitive presets that deliver optimized screen performance in different applications. Besides, Flicker-Free technology and a Blue Light Filter help to eliminate eyestrain from extended viewing periods for improved productivity. A VESA-compatible mount adapts easily to multi-monitor or wall-mount set ups.



1. VESA Compatible(Wall Mount 75x75mm)
2. Menu Control Panel
3. AC In
4. VGA
5. HDMI

Visit Us  www.viewsonic.com

DISPLAY

Display Size (in.):	22
Viewable Area (in.):	21.5
Panel Type:	TN Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	600:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + Hi-FRC)
Aspect Ratio:	16:9
Response Time (Typical Tr+Tf):	5ms
Viewing Angles:	90° horizontal, 65° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102% size (Typ)
Pixel Size:	0.248 mm (H) x 0.248 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
HDMI 1.4:	1
Power in:	External power adapter

POWER

Eco Mode (Conserve):	18W
Eco Mode (optimized):	20W
Consumption (typical):	22W
Consumption (max):	24W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.3W
Power Supply:	External

CONTROLS

Physical Controls:	Auto, -, +, Menu, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	75 x 75 mm
------------------	------------

INPUT SIGNAL

Frequency Horizontal:	24 ~ 82KHz
Frequency Vertical:	50 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4)
Analog Sync:	Separate - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	-4° / 14°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	4.6
Net Without Stand (lbs):	4
Gross (lbs):	6.6

WEIGHT (METRIC)

Net (kg):	2.1
Net Without Stand (kg):	1.8
Gross (kg):	3

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	22.1 x 14.4 x 4.3
Physical (in.):	20.1 x 14.6 x 7.3
Physical Without Stand (in.):	20.1 x 12.2 x 1

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	562 x 365 x 110
Physical (mm):	510 x 370 x 185
Physical Without Stand (mm):	510 x 310 x 25

GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, PSB, BIS
PACKAGE CONTENTS:	VA2223-H x1, HDMI Cable (v1.4; Male-Male), AC/DC Adapter x1, Quick Start Guide x1, Power plug x2
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market