



## Fitur Utama

- SXGA resolution
- SuperClear® technology
- Flicker-Free and Blue Light Filter
- ViewMode technology
- Eco-mode



## Deskripsi Produk

ViewSonic VA951S 19" LED display with 5:4 aspect ratio that is perfect for legacy or customized applications in corporate, government, educational and other vertical markets. Featuring crystal-clear 1280 x 1024 resolution, SuperClear® technology and 20M:1 DCR, the display presents sharp, true and consistent color performance at 178°/178°-wide viewing angles. Uniform and matte bezel provide easy configuration for multi display setup. DVI and D-Sub inputs offer easy connectivity to desktops or laptops, and ViewSonic's exclusive ViewMode delivers optimized color rendering for different viewing scenarios. Flicker-Free and Blue Light Filter minimize eye fatigue and deliver comfortable viewing experience for all applications. Energy Star and EPEAT certified, the VA951S's embedded ECO mode also cuts power consumption by up to 50%, and comes with a VESA-compliant mount for more flexible installation in your organization.

**Kunjungi Kami** ■ [www.viewsonic.com](http://www.viewsonic.com)

**LCD**

Type:	19" Color a-Si TFT Active Matrix 1280x1024 LCD
Display Area:	19 inch
Optimum Resolution:	1280x1024
Rasio Kontras:	1000 :1 (typical), 20,000,000:1 (DCR)
Kecerahan:	250 cd/m <sup>2</sup> (typ)
Sudut Pandang:	178° horizontal, 178° vertical
Waktu merespon:	5ms?GtGσ?
Refresh Rate (Hz):	75
Panel Surface:	Anti-Glare type, Hard- coating (3H)
Sumber cahaya:	30000 Hrs (Min)
Waktu merespon:	5ms?GtGσ?

**VIDEO INPUT**

Analog:	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p)
Digital:	DVI (TMDS, 100 ohms)
Frequency:	Fh: 24-82KHz; Fv: 50- 75Hz
Sync:	Separate Sync

**KESESUAIAN**

PC:	PC Compatibles (from VGA up to 1280 x 1024 Non Interlaced)
Mac:	Power Mac (up to 1280 x 1024 )

**ERGONOMIS**

Memiringkan:	-5° ~ +25°
--------------	------------

**KONEKTOR**

Analog:	DB-15 x1
Digital:	DVI-D x1
Power:	3-pin plug (CEE22) x1

**POWER**

Tegangan:	AC 100-240V (Universal); 50/60 Hz
Konsumsi:	20W; Optimize:16W; Conserve:13W

**OPERATING CONDITIONS**

Suhu:	32°F to 104°F (0°C to 40°C)
Kelembaban:	20% to 90% (no condensation)

**UKURAN**

Physical:	416.2mm (width) x 402.2mm (height) x 199.1mm (depth)
-----------	--

**BERAT**

Bersih:	3.0 kg
---------	--------

**REGULASI**

cULus, FCC-B, ICES003, Energy Star 8.0, EPEAT Bronze,  
CEC, MX-CoC, Mexico Energy, REACH, WEEE, TGM,  
CCC, China RoHS, China Energy Label, CECP

**PEMASANGAN DI DINDING**

VESA® 100x100 mm

**PACKAGE CONTENTS**

LCD Display,  
Power Cable,  
VGA Cables,  
Quick Start Guide,  
ViewSonic Wizard CD-ROM