

ViewSonic® LCD DISPLAY VG2448

Key Features

- vDisplay Manager (free download)
- Narrow bezel
- HDMI, DisplayPort and VGA inputs
- SuperClear® IPS technology
- Versatile stand design



Product Description

ViewSonic VG2448 is a 24" (23.8" viewable) 1080p monitor with productivity enhancing features including IPS technology and an advanced ergonomic design for the modern day office. Utilising SuperClear® IPS technology and 1080p resolution, VG2448 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customisable adjustments currently available to provide maximum comfort, including dual direction pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2448 uses environmentally friendly packaging and offers quick and easy out-of-the-box set-up via the Quick Release stand. The cloud client mountable stand coupled with cable management design features, makes VG2448 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.0 inputs.



Visit Us  www.viewsonic.com

DISPLAY

Monitor Size:	24"W (23.8" Viewable)
Panel Technology:	SuperClear® IPS TFT LCD
Resolution:	FHD 1920 x 1080
Display Area:	527.04 mm (H) x 296.46 mm (V)
Aspect Ratio:	16:9
Brightness:	250 cd/m ² (Typ)
Contrast Ratio:	1000:1 (Typ)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angle:	178 / 178 (Typ)
Response Time:	5ms (GtG)
Refresh Rate (Hz):	60

Colour Gamut:

Adobe RGB: 77% size / 72% coverage (Typ)
 NTSC: 72% size (Typ)
 sRGB: 103% size / 92% coverage (Typ)

INPUT SIGNAL

Frequency:	Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz
Sync:	Separate Sync / Composite Sync / Sync on Green

COMPATIBILITY

PC:	Windows 7, Windows 8, Windows 10 certified
Mac®:	Power Mac tested

CONNECTOR

Digital:	HDMI x 1 (v1.4 compatible) DisplayPort x 1 (v1.2 compatible)
Analog:	VGA x 1

SPEAKERS

2W x 2

USB

Up Stream:Type B x 1 Down Stream:Type A x 4
--

POWER

Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	21W
Optimize:	18W
Conserve:	15W

ERGONOMICS

Tilt:	40 ~ -5 degrees
Swivel:	120 degrees
Pivot:	180 degrees
Height Adjustment:	0 ~ 130mm

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	549 mm (W) x 517 mm (H) x 202 mm (D)
Physical without stand (mm):	549 mm (W) x 326 mm (H) x 50 mm (D)
Packaging (mm):	604 mm (W) x 385 mm (H) x 210 mm (D)

WEIGHT

Net with stand (kg):	5.82kg
Net without stand (kg):	3.44kg
Gross (kg):	8.71 kg

REGULATIONS

cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, S-mark, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC, UkrSEPRO, GS, BSMI, RCM, GEMS, VCCI, PSE, BIS, CCC, China RoHS, China Energy Label

PACKAGE CONTENTS

LCD Display Power Cable DisplayPort Cable USB3.0 Upstream Cable Quick Start Guide
*Actual content may differ from market to market