

# ViewSonic® LCD DISPLAY VX2476-SH

## Key Features

- SuperClear® IPS panel for vivid picture quality and wider viewing angles
- Frameless bezel and stylish stand
- 75Hz Refresh Rate delivers fluid visuals
- Flexible connectivity with VGA and two HDMI ports
- User-customized and pre-calibrated ViewMode for every scenario



## Product Description

Whether for office use or for enjoying entertainment at home, the ViewSonic® VX2476-SH is designed to take your viewing experience to another level. With a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. The Full HD resolution boosts efficiency and image detail needed for work or play. A mega dynamic contrast ratio of 80M:1 delivers enhanced image depth for a better user experience. The Built-in HDMI and VGA inputs deliver flexible connectivity options for a wide range of devices.

Visit Us  [www.viewsonic.com](http://www.viewsonic.com)

DISPLAY		DIMENSIONS (IMPERIAL) (WXHxD)	
Display Size (in.):	24	Packaging (in.):	24.5 x 16.6 x 4.3
Viewable Area (in.):	23.8	Physical (in.):	21.2 x 15.8 x 7.2
Panel Type:	IPS Technology	Physical Without Stand (in.):	21.2 x 12.5 x 1.7
Resolution:	1920 x 1080	DIMENSIONS (METRIC) (WXHxD)	
Resolution Type:	FHD	Packaging (mm):	623 x 421 x 109
Static Contrast Ratio:	1,000:1 (typ)	Physical (mm):	539 x 402 x 184
Dynamic Contrast Ratio:	80M:1	Physical Without Stand (mm):	539 x 316 x 43
Light Source:	LED	GENERAL	
Brightness:	250 cd/m <sup>2</sup> (typ)	Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI
Colors:	16.7M	PACKAGE CONTENTS:	VX2476-SH x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick Start Guide x1
Color Space Support:	8 bit (6 bit + Hi-FRC)	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Aspect Ratio:	16:9	Warranty:	*Warranty offered may differ from market to market
Response Time (Typical GTG):	4ms	Country Of Origin:	China
Viewing Angles:	178° horizontal, 178° vertical	1. The Max. refresh rate may vary by I/O port, resolution, user environment and setti please check the the "Specifications" section in the <a href="#">user guide</a> .	
Backlight Life (Hours):	30000 Hrs (Min)		
Curvature:	Flat		
Refresh Rate (Hz):	Max. 75Hz (RGB Analog, HDMI (v1.4)) (Max) <sup>1</sup>		
Blue Light Filter:	Yes		
Flicker-Free:	Yes		
Color Gamut:	NTSC: 72% size (Typ), sRGB: 100% size (Typ)		
Pixel Size:	0.275 mm (H) x 0.275 mm (V)		
Surface Treatment:	Anti-Glare, Hard Coating (3H)		
COMPATIBILITY			
PC Resolution (max):	1920x1080		
Mac® Resolution (max):	1920x1080		
PC Operating System:	Windows 10 certified; macOS tested		
Mac® Resolution (min):	1920x1080		
CONNECTOR			
VGA:	1		
3.5mm Audio Out:	1		
HDMI 1.4:	2		
Power in:	3-pin Socket (IEC C14 / CEE22)		
POWER			
Eco Mode (Conserve):	16W		
Eco Mode (optimized):	19W		
Consumption (typical):	22W		
Consumption (max):	23W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	Internal		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	75 x 75 mm		
INPUT SIGNAL			
Frequency Horizontal:	15 ~ 83KHz		
Frequency Vertical:	50 ~ 75Hz		
VIDEO INPUT			
Digital Sync:	TMDS - HDMI (v1.4)		
Analog Sync:	Separate - RGB Analog		
ERGONOMICS			
Tilt (Forward/Back):	-3° / 15°		
WEIGHT (IMPERIAL)			
Net (lbs):	7.7		
Net Without Stand (lbs):	6.8		
Gross (lbs):	10.5		
WEIGHT (METRIC)			
Net (kg):	3.5		
Net Without Stand (kg):	3.1		
Gross (kg):	4.8		