

ProID Series

Physical Access Readers



ProID10



ProID40



ProID20



ProID30

The ProID family of card readers is designed to offer card technologies options to customers such as 125KHz EM, 13.56MHz IC, DESFire, FeliCa or Legic.

With a robust all-weather protection and a beautiful modern design, the ProID family is the best choice for indoor or outdoor applications.

Features

- High stability and energy efficiency.
- LED light and touch keypad.
- On-site adjustable Wiegand output (26 or 34 bits).
- Waterproof design suitable for indoor or outdoor applications.
- Black or white color available.

Specifications (G: GLExclusive Feature)

Read Range ProID10 EM/IC 3.5cm. ProID20/30/40 EM/IC 5cm.	Output Format G Wiegand 26bit or 34bit Adjustable	Operating Humidity 10% ~ 90% Relative Humidity Non-Condensing
Reading Time ≤300ms	Power Operating Voltage 7~13VDC Current Draw < 80mA	Audio Beep
Input Port External LED Control External Buzzer Control	LED Pulsing White Standby Light Red and Green LEDs	G Index Protection IP65
Material ABS+PC	Operating Temperature -20 °C ~ 65 °C	Dimensions ProID10: 80.5 × 44 × 15mm. ProID20/30: 90 × 90 × 16mm. ProID40: 116 × 75 × 15mm.

How to Order ProID Series?

ProID20 WE-RS

